




## Dimensions



measurements in mm

Cutout: 150mm




Colours also available




Any RAL colour (special request)



Vinyl wrap available



355°



90°



DALI & Phase Cut Dimming Available



IP20







CE



RoHS

## Product details

Other wattages available, please contact us for details.

System Power	14W			20W			33W					
CCT	2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K			
Luminaire Lumens at CRI 85*	1536	1584	1664	2136	2204	2316	3232	3332	3500			
Luminaire Lumens at CRI 90+*	1260	1340	1380	1752	1864	1920	2648	2820	2904			
LED Efficacy @ CRI 85	109.7 lm/W	113.1 lm/W	118.9 lm/W	106.8 lm/W	110.2 lm/W	115.8 lm/W	97.9 lm/W	101 lm/W	106.1 lm/W			
LED Efficacy @ CRI 90+	90 lm/W	95.7 lm/W	98.6 lm/W	87.6 lm/W	93.2 lm/W	96 lm/W	80.2 lm/W	85.5 lm/W	88 lm/W			
Optics	 15°			 24°			 36°			 60°		

\*Lumen values may vary by +/- 10%

For more information visit [shoplight.lighting](https://shoplight.lighting)